

---

# Physics based turbine performance assessment using wind flow models.

---

Samuel Davoust, PhD  
Co-founder & Tech lead

[samuel.davoust@tipspeed.com](mailto:samuel.davoust@tipspeed.com)

Poster P007

“Is it underperformance  
or lack of resource?”

“Is it underperformance  
or lack of resource?”


**Knowing the absolute  
performance is hard**

**Finding optimization  
opportunities is challenging**

**Changes over time  
can be missed**


# A digital twin from *resource* to *production*

## Set-up wind farm Digital twin




10 min time series as independent references for wind, losses and power, at each turbine

## Compare to asset (SCADA)



Predicted vs actual power directly compared for each turbine, across entire site

## Categorize & quantify losses




Enables assessment, quantification and root causes investigation of underperformances


# Technology stack (patent pending)




## Data sources




## Digital twin



## Insights



## Actions



**Adapts to different scenarios**  
Combines existing data,  
models & tools

**10 min timeseries at turbine level**  
Automated workflows optimized for  
10 min timeseries at turbine level

**Goal = real world applications**  
Analyses & Validations based on all  
conditions including wakes

# Validation method and dataset


## Goal

Evaluate wind speed accuracy during operational period

## Digital twin setup

Wind speed calibrated only with pre-construction measurements  
Wake model tuned with 1 year of production data

## Procedure



## Validation data

12 calibrated operational sensor (masts, nacelle lidar, spinner anemometers) across 4 farms  
Turbines in operation, including wakes  
Durations ranging from 3 weeks to 1 year

Type	Distance	Time gap
Complex	1.5 km	4 years
Complex	1.6 km	3 years
Simple	0 km	1 year
Simple	4 km	10 years

## Metrics calculated on 10 min timeseries


Mean wind speed bias, Mean absolute error,  
Correlation coefficient

# Wind validation results including wakes

## Results \*

Bias (m/s)	$0.02 \pm 0.08$
Absolute bias (m/s)	$0.09 \pm 0.04$
MAE (m/s)	$1.14 \pm 0.19$
Correlation (-)	$0.79 \pm 0.10$

\* Site aggregated, then averaged



# Wind validation results including wakes

Results *	
Bias (m/s)	$0.02 \pm 0.08$
Absolute bias (m/s)	$0.09 \pm 0.04$
MAE (m/s)	$1.14 \pm 0.19$
Correlation (-)	$0.79 \pm 0.10$


\* Site aggregated, then averaged

**What real world performance applications can be achieved?**




# From wind farm performance screening to root cause analysis


## Step 1: assess performance ratios



## Step 2: check individual PC




## Step 3: identify root cause




Using Tipspeed data on all turbines simultaneously allowed to detect unknown under performances and uncover potential root cause (pitch). OEM engaged for resolution.

# From wind farm performance screening to root cause analysis

10 min wind speed accuracy



Yaw misalignment




**Tipspeed: 0.3°**

**Nacelle lidar: 0.4°**

<b>Site</b>	Complex terrain.
<b>Context</b>	Suspicion of performance issues. Past nacelle lidar campaign showed good performance on target turbine.
<b>Test method</b>	Blind validation of wind speed accuracy against lidar. Ability to detect under performance.


# Validating the detection of a performance issue over time



**Tipspeed correctly identified under performance (turbines, periods and magnitude)**

<b>Site</b>	Complex terrain.
<b>Context</b>	Significant performance issues previously diagnosed. Unperformance events and magnitude known.
<b>Test method</b>	Blind validation of Tipspeed prediction of impacted turbines, time periods and magnitude of underperformances.

# Validation of yaw misalignment detection and its impact on performance



**Tipspeed blindly predicted the dates of events, and the misalignments before/after offsets.**

<b>Site</b>	Simple terrain.
<b>Context</b>	Site dedicated to yaw experiments. Misalignments known to customer, before and after offsets applied.
<b>Test method</b>	Blind validation of Tipspeed prediction of pre/post misalignments, and dates of events.

- **Continue to implement new validation methods for long duration wind predictions within operating wind farms.**
- **Report on our on-going multi-site validation of yaw misalignment predictions.**
- **Implement data fusion of the digital twin together with sensors, in the case where reliable operational data is available.**

---

# A special thanks to our early partners for their trust

---

 Tipspeed

**BORALEX**

 energie  
**TEAM**

 **ENGie**  
Green

 **INNERGEX**

 **valeco**  
PRODUCTEUR D'ÉNERGIES  
RENOUVELABLES

 **VALOREM**  
L'ÉNERGIE D'AGIR